

North Fork Reloading Data

460 Weatherby Magnum



Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs of excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Weatherby Mark V

Barrel length: 26" (66cm)

Primer: CCI 250

Case: Weatherby (Norma)

North Fork Semi Spitzer (SS)

Bullet diameter: .458"

Max COL: 3.750" (95,2mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
400	Re17	108.6			118	2 860	872
400	H414	108.6			118	2 800	853
450	Re17	102.1			111	2 700	823
450	H414	100.3			109	2 620	799
500	RE19	104.0			113	2 560	780
500	H414	99.4			108	2 550	777
500	Re19	103.0			112	2 500	762
500	Norma 204	101.2			110	2 500	762
550	Re19	97.5			106	2 400	732
550	IMR7828SSC	101.2			110	2 450	747