

HUBLOT 6 UP TWIN



Certificate model name : HUBLOT 6 UP T1



AIR - Pellet stoves

CADEL

Nominal power	kW	6
Reduced power	kW	3
Introduced thermal power (max)	kW	7.1
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Seasonal energy efficiency	ηs [%]	84
Nominal efficiency	%	88
Reduced efficiency	%	90
Heating volume (min-max)	m³	84 - 168
Nominal CO at 13% O ₂	%	0.013
Reduced CO at 13% O ₂	%	0.024
Emissions CO (13% O ₂) (min-max)	mg/Nm³	297 - 160
Emissions OGC (13% O ₂) (min-max)	mg/Nm³	5 - 3
Emissions NOX (13% O ₂) (min-max)	mg/Nm³	120 - 140
Dust content at 13% O ₂ (min-max)	mg/Nm³	20 - 15
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	11
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	0.7 - 1.5
Autonomy (min-max)	h	7 - 16
Ignition electrical absorption (max)	W	340
Operating electrical absorption (max)	W	106
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	12
Mass of smoke (min-max)	g/sec	3.1 - 6
Exhaust fumes temperature (max)	°C	211
Net weight	kg	120
Gross weight	kg	135
Exhaust fumes (A)	Ø mm	80
Hole combustion air inlet (B)	Ø mm	130
Ducting outlet (C)	Ø mm	-
Ducting capability up to	m	-



Art. 15A-B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



MATCH

7023038



Black steel /cast iron

EAN 8053859019282

PLUS



Sealed chamber



Bluetooth



Connection to the room thermostat



Concentric kit



Integrated Wi-Fi



Cast iron burning pot



Daily weekly programming



Go fast - faster pellet ignition



Cast iron inner




Comfort mode



Upper exhaust


STOVE PACKING



L (cm)	H (cm)	P (cm)
79	93,9	70

VOLUME (m³)
0,52

ACCESSORIES




L (cm)	H (cm)	P (cm)

STOCKING



Nr (max)
2

TRANSPORT



57 pcs