



USTM

Professional
water filters

INNOVATION SAFETY CONVENIENCE



IZZI

- **PATENTED SOLUTIONS**
- **ENHANCED DURABILITY DUE TO THE USE OF PET MATERIAL UP TO 10 BAR**
- **HYGIENIC CARTRIDGE REPLACEMENT**
- **INNOVATIVE 'IZZI CLEAN' WATER DRAIN (optional)**
- **QUICK INSTALLATION**
- **CONVENIENT INSTALLATION – FROM THE LEFT OR RIGHT SIDE OF THE PIPE**
- **INCREASED WATER FLOW**
- **'CLICK' SYSTEM TO PREVENT OVER-TIGHTENING**
- **BRASS COUPLINGS WITH SEALS**

Symbol	WF 1 IZZI kpl
Stages of filtration	1
Dimensions	14/15/37 cm
Connection	3/4"
Cartridge size	10"
Max. operating pressure	10 bar
Operating temperature	2-35°C
Water flow	2m ³ /h

ENTRY 2 IZZI

- patented innovative solutions
- increased durability thanks to the use of PET material
- hygienic cartridge replacement
- quick installation
- convenient fitting – on the left or right-hand side
- increased water flow
- 'Click' system to prevent twisting
- innovative 'IZZI CLEAN' flush (optional)
- brass half-couplings with seals

Symbol	ENTRY 2 IZZI
Stages of filtration	2
Dimensions	30/15/37 cm
Connection	3/4"
Cartridge size	10"
Max. operating pressure	10 bar
Operating temperature	2-35°C
Water flow	2m ³ /h



ENTRY 3 IZZI

- patented innovative solutions
- increased durability thanks to the use of PET material
- hygienic cartridge replacement
- quick installation
- convenient fitting – on the left or right-hand side
- increased water flow
- 'Click' system to prevent twisting
- innovative 'IZZI CLEAN' flush (optional)
- brass half-couplings with seals


Symbol	ENTRY 3 IZZI
Stages of filtration	3
Dimensions	45/15/37 cm
Connection	3/4"
Cartridge size	10"
Max. operating pressure	10 bar
Operating temperature	2-35°C
Water flow	2m ³ /h



**IZZI Clean drain
(optional)**



**Safety
clip**



**Air vent makes it easier
to replace the cartridge**