

QUASIMODO^3 UP

AIR - Pellet stoves



Nominal power	kW	**9,3**
Reduced power	kW	**2,7**
Introduced thermal power (max)	kW	**10,5**
Nominal water useful power	kW	**-**
Reduced water useful power	kW	**-**
Nominal efficiency	%	**89**
Reduced efficiency	%	**93,9**
Heating volume (min-max)	m^3	**65 - 223**
Nominal CO at 13% O_2	%	**0,009**
Reduced CO at 13% O_2	%	**0,021**
Emissions CO (13% O2) (min-max)	mg/Nm^3	**265 - 107**
Emissions OGC (13% O2) (min-max)	mg/Nm^3	**3,2 - 2,1**
Emissions NOX (13% O2) (min-max)	mg/Nm^3	**108 - 119**
Dust content at 13% O_2 (min- max)	mg/Nm^3	**18 - 18,8**
Boiler capacity (H_2O)	l	**-**
Hopper capacity	kg	**11,5**
Combustible		**Pellet ø6**
Hourly consumption (min-max)	kg/h	**0,59 - 2,18**
Autonomy (min-max)	h	**5,3 - 19**
Ignition electrical absorption (max)	W	**346**
Operating electrical absorption (max)	W	**113,7**
Supply and frequency	V - Hz	**230 - 50**
Chimney flue depression	Pa	**11,8**
Exhaust diameter	mm	**80**
Combustion air inlet diameter	mm	**60**
Mass of smoke (min-max)	g/sec	**2,8 - 5,7**
Exhaust fumes temperature (max)	°C	**190**
Net weight	kg	**108**
Gross weight	kg	**121**
Exhaust fumes	see	**A**
Hole combustion air inlet	see	**B**
Ducting outlet	see	**-**
Ducting capability up to	m	**-**






MATCH

7020058	Black steel	EAN 8053859013358

PLUS

- Sealed chamber
- Integrated Wi - Fi
- Cast iron inner
- Bluetooth
- Cast iron burning pot
- Comfort mode
- Connection to the room thermostat
- Daily weekly programming
- Upper exhaust
- Concentric kit


STOVE PACKING



L (cm)	H (cm)	P (cm)
80	**75**	**70**

VOLUME (m^3)
0,42

ACCESSORIES




	L (cm)	H (cm)	P (cm)
Stand	**80**	**42**	**56**

STOCKING



Nr (max)
2

TRANSPORT



57 pcs