




G Model - Micrometer Adjustable (Click) Torque Wrench

- All steel construction, superb durability.
- Permanently stamped major and minor scales for precision torque values setting.
- Convenient Metric or English major scale with English or Metric secondary scale.
- +/-4% Accuracy in clockwise direction from 20% to 100% Max.Torque.
- Pull/push to unlock/lock the locking ring to setting torque.
- Grooved non-slip grip fits comfortably in your hand.
- Various kinds of heads designed for different applications:
 - GM / G model: Fine-tooth ratchets suitable for operation in confined spaces requiring only 8 degrees swing.
 - GMH / GH model: Head holder for standard 9x12 and 14x18mm rectangular shank heads.
 - GMR model: Round head holders for $\Phi 16$, $\Phi 22$ mm heads.



Clear Scale



1

Pull and hold
the locking ring



2

Rotate the locking ring to adjust
the torque by the other hand



3

Release the locking ring
after torque being set

100% Calibrated

Unique serial number for each torque wrench,
corresponding to the certificate of calibration



Shockproof packaging

Specially designed for all series of
"NovaTork" torque products




GM

Reversible Ratchet Head G Torque Wrench

Bi-direction operation, 8 degrees swing, suitable for confined space

G (English unit)



(Metric)

Item No.	Square Drive	Torque Range		Increment	Length mm	Width mm	Weight kg
		N.m	Lb.ft				
GM112	1/4"	2.5-12	20-105*	0.05	290	38	0.68
GM120	1/4"	4.0-20	30-180*	0.1	290	38	0.68
GM230	3/8"	6.0-30	50-250*	0.1	318	38	0.82
GM330	1/2"	6.0-30	50-250*	0.1	318	38	0.82
GM260	3/8"	10-60	9-45	0.25	388	38	0.96
GM360	1/2"	10-60	9-45	0.25	388	38	0.96
GM2100	3/8"	20-100	15-75	0.5	443	38	1.04
GM3100	1/2"	20-100	15-75	0.5	443	38	1.04
GM2125	3/8"	25-125	20-90	0.5	443	38	1.04
GM3125	1/2"	25-125	20-90	0.5	443	38	1.04
GM3200	1/2"	40-200	30-150	1	468	40	1.16
GM3335	1/2"	65-335	50-250	1	528	40	1.3
GM4335	3/4"	65-335	50-250	1	528	40	1.34
GM4500	3/4"	100-500	80-400	2.5	855	60	5
GM4800	3/4"	160-800	120-600	4	1055	60	5.9
GM5800	1"	160-800	120-600	4	1055	60	5.9
GM41000	3/4"	200-1000	150-750	5	1055	60	5.9
GM51000	1"	200-1000	150-750	5	1055	60	5.9
GM51500	1"	300-1500	200-1100	5	1260	75	9.2
GM52000	1"	400-2000	300-1500	10	1260	75	9.2
GM53000	1"	600-3000	400-2000	15	1260	75	10.5
GM3200L	1/2"	40-200	30-150	1	525	40	1.29
GM3335L	1/2"	65-335	50-250	1	700	40	2.1
GM4335L	3/4"	65-335	50-250	1	700	40	2.15
GM51500L	1"	300-1500	200-1100	5	1600	75	13
GM52000L	1"	400-2000	300-1500	10	1600	75	13
GM53000L	1"	600-3000	400-2000	15	1840	75	15.2
GM4400S	3/4"	80-400	60-300	2	710	57	3
GM4500S	3/4"	100-500	80-400	2.5	710	57	3

*Unit is Lb.in; L is extended length version; S is shorten length version.

(English)

Item No.	Square Drive	Torque Range		Increment	Length mm	Width mm	Weight kg
		Lb.ft	N.m				
G1200	1/4"	40-200*	4.0-22	1.0*	280	38	0.68
G2250	3/8"	50-250*	6.0-30	1.0*	315	38	0.82
G2100	3/8"	20-100	25-135	0.5	425	38	1.04
G3100	1/2"	20-100	25-135	0.5	425	38	1.04
G3150	1/2"	30-150	40-200	0.5	505	40	1.16
G3250	1/2"	50-250	70-340	1	525	40	1.3
G4250	3/4"	50-250	70-340	1	525	40	1.34
G4400	3/4"	80-400	100-550	2	855	60	5
G4600	3/4"	100-600	150-800	2.5	1055	60	5.9
G5600	1"	100-600	150-800	2.5	1055	60	5.9
G51000	1"	200-1000	250-1350	5	1260	75	9.2
G52000	1"	400-2000	500-2700	10	1260	75	10.5
G3250L	1/2"	50-250	70-340	1	705	40	2.1
G4250L	3/4"	50-250	70-340	1	705	40	2.15

*Unit is Lb.in; L is extended length version.

GMH

Rectangular Shank Head G Torque Wrench

for 9x12, 14x18, 24x32, 27x36mm rectangular shank head inserts

GH (English unit)



(Metric)

Item No.	Shank Size mm	Torque Range		Increment	Length mm	Width mm	Weight kg
		N.m	Lb.ft				
GMH912	9x12	2.5-12	20-105*	0.05	287	38	0.58
GMH920	9x12	4.0-20	30-180*	0.1	287	38	0.58
GMH930	9x12	6.0-30	50-250*	0.1	306	38	0.72
GMH960	9x12	10-60	9-45	0.25	375	38	0.86
GMH9100	9x12	20-100	15-75	0.5	430	38	0.94
GMH9125	9x12	25-125	20-90	0.5	430	38	0.94
GMH14200	14x18	40-200	30-150	1	467	38	1.06
GMH14335	14x18	65-335	50-250	1	527	38	1.2
GMH14400	14x18	80-400	60-300	2	697	35	2
GMH24500	24x32	100-500	80-400	2.5	855	56	5
GMH24800	24x32	160-800	120-600	4	1055	56	5.9
GMH241000	24x32	200-1000	150-750	5	1055	56	5.9
GMH271500	27x36	300-1500	200-1100	5	1249	64	9
GMH272000	27x36	400-2000	300-1500	10	1249	64	9
GMH273000	27x36	600-3000	400-2000	15	1249	64	10.3
GMH14335L	14x18	65-335	50-250	1	700	38	2
GMH24400S	24x32	80-400	60-300	2	710	56	2.8
GMH24500S	24x32	100-500	80-400	2.5	710	56	3

*Unit is Lb.in; L is extended length version; S is shorten length version.

(English)


Item No.	Shank Size mm	Torque Range		Increment	Length mm	Width mm	Weight kg
		Lb.ft	N.m				
GH9200	9x12	40-200*	4.0-22	1*	268	38	0.58
GH9250	9x12	50-250*	6.0-30	1*	303	38	0.72
GH9100	9x12	20-100	25-135	0.5	413	38	0.94
GH14150	14x18	30-150	40-200	0.5	507	38	1.06
GH14250	14x18	50-250	70-340	1	527	38	1.2
GH24400	24x32	80-400	100-550	2	855	56	5
GH24600	24x32	100-600	150-800	2.5	1055	56	5.9
GH271000	27x36	200-1000	250-1350	5	1260	64	9
GH272000	27x36	400-2000	500-2700	10	1260	64	10.3

*Unit is Lb.in

GMR

Round Head Holder G Torque Wrench

for $\Phi 16$, $\Phi 22$ mm round hole inserts



(Metric)

Item No.	Round hole mm	Torque Range		Increment N.m	Length mm	Width mm	Weight kg
		N.m	Lb.ft				
GMRI 612	$\Phi 16$	2.5-12	20-105*	0.05	288	38	0.58
GMRI 620	$\Phi 16$	4.0-20	30-180*	0.1	288	38	0.58
GMRI 630	$\Phi 16$	6.0-30	50-250*	0.1	307	38	0.72
GMRI 660	$\Phi 16$	10-60	9-45	0.25	377	38	0.86
GMRI 6125	$\Phi 16$	25-125	20-90	0.5	431	38	0.94
GMRI 6200	$\Phi 16$	40-200	30-150	1	455	38	1.06
GMRI 6335	$\Phi 16$	65-335	50-250	1	515	38	1.2
GMRI 6400	$\Phi 16$	80-400	60-300	2	695	38	2
GMR22500	$\Phi 22$	100-500	80-400	2.5	800	38	4.3
GMR22800	$\Phi 22$	160-800	120-600	4	1005	38	5.2
GMR221000	$\Phi 22$	200-1000	150-750	5	1005	38	5.2
GMRI 6335L	$\Phi 16$	65-335	50-250	1	695	38	2

*Unit is Lb.in; L is extended length version

【For English unit, please contact the manufacturer】



GM_E

Reversible Ratchet Head G Torque Wrench

With Extension



(Metric)

Item No.	Square Drive	Torque Range		Increment N.m	Length mm	Width mm	Weight kg	Extension
		N.m	Lb.ft					
GM51500E	1"	300-1500	200-1100	5	2200	75	12.10	1
GM52000E	1"	400-2000	300-1500	10	2200	75	12.10	1
GM53000E	1"	600-3000	400-2000	15	2780	75	15.50	1

GMH_E

Rectangular Shank Head G Torque Wrench

With Extension



(Metric)

Item No.	Shank Size mm	Torque Range		Increment N.m	Length mm	Width mm	Weight kg	Extension
		N.m	Lb.ft					
GMH271500E	27x36	300-1500	200-1100	5	2200	64	12.50	1
GMH272000E	27x36	400-2000	300-1500	10	2200	64	12.50	1
GMH273000E	27x36	600-3000	400-2000	15	2780	64	15.30	1

Note: Due to the product improvement, the technical parameters are subject to variation, please refer to the actual production from the factory.