

BQ Series Torque Wrench with Quick Release

- Accuracy is ±4% from 20-100% of capacity.
- All metal structure, alloy steel pipe, durable.
- Clear scale, easy to read.
- Minor scale is 1/10 of increment of main scale.
- Pull to unlock lock ring keeps selected torque secure from accidental change.
- Quick release head.
- Grooved non-slip grip.



BQLM-QR With Reversible Ratchet Head

Bi-directional operation, suitable for confined space

Item No.	Square Drive	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
BQLM260-QR	3/8"	10-60	0.5	389	33	0.94
BQLM360-QR	1/2"	10-60	0.5	389	33	0.94
BQLM2100-QR	3/8"	20-100	0.5	428	33	1.04
BQLM3150-QR	1/2"	30-150	1	466	40	1.05
BQLM3220-QR	1/2"	40-220	1	507	40	1.16
BQLM3350-QR	1/2"	70-350	2	567	40	1.34
BQLM3400-QR	1/2"	80-400	2	620	40	1.36

Large Size (Non-Quick Release)

Item No.	Square Drive	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
BQLM4600	3/4"	100-600	2.5	1060	64	5.1
BQLM4800	3/4"	150-800	5	1250	64	5.9
BQLM51000	1"	200-1000	5	1250	71	7
BQLM51500E	1"	300-1500	10	1870	71	10.5
BQLM52000E	1"	400-2000	10	1870	71	10.5

Mini Size for BQLM-QR

Item No.	Square Drive	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
BQLSM15-QR	1/4"	1.0-5	0.05	217	28	0.3
BQLSM110-QR	1/4"	2.0-10	0.1	227	28	0.32
BQLSM125-QR	1/4"	5.0-25	0.2	265	28	0.33
BQLSM225-QR	3/8"	5.0-25	0.2	265	28	0.35



BMH-QR With Rectangular Shank Head Holder

for 9x12mm,14x18mm rectangular shank head inserts

Item No.	Shank Size mm	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
BMH960-QR	9×12	10-60	0.5	390.5	22	0.96
BMH9100-QR	9×12	20-100	0.5	445.5	22	1.04
BMH14150-QR	14×18	30-150	1	453.3	32	1.05
BMH14220-QR	14×18	40-220	1	474.3	32	1.16
BMH14350-QR	14×18	70-350	2	537.3	32	1.34
BMH14400-QR	14×18	80-400	2	593.3	32	1.36

Mini Size for BMH-QR

Item No.	Shank Size mm	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
BMH95S-QR	9×12	1.0-5	0.05	200	22	0.32
BMH910S-QR	9×12	2.0-10	0.1	210	22	0.33
BMH925S-QR	9×12	5.0-25	0.2	248	22	0.35

Note: Due to the product improvement, the technical parameters are subject to variation, please confirm with the supplier when placing an order.

100% Calibrated

Unique serial number for each torque wrench, corresponding to the certificate of calibration



Shockproof packaging

Specially designed for all series of "NovaTork" torque products

