


P Model - Preset Torque Wrench

- Easy to adjust to desired torque (in the tool room, appropriate torque tester is required).
- Do not allow to adjust torque value randomly.
- +/-4% Accuracy in Clockwise direction from 20% to 100% Max. Torque.
- Various kinds of heads designed for different applications:
 - P model: Reversible ratchet head for clockwise and counter-clockwise operation.
 - PH model: Head holder for standard 9x12, 14x18, 24x32, 27x36mm square shank heads.

P

Reversible Ratchet Head P Torque Wrench

Bi-directional operation, 8 degrees swing, suitable for confined space



Matching sockets


Item No.	Square Drive	Torque Range		Length mm	Width mm	Weight kg
		N.m	Lb.ft			
P112	1/4"	2.5-12	20-105*	276	38	0.55
P120	1/4"	8-20	60-180*	276	38	0.55
P230	3/8"	10-30	90-250*	306	38	0.68
P330	1/2"	10-30	90-250*	280	38	0.62
P260	3/8"	20-60	15-45	320	38	0.76
P360	1/2"	20-60	15-45	320	38	0.76
P2125	3/8"	50-125	40-90	400	38	0.84
P3125	1/2"	50-125	40-90	400	38	0.84
P3200	1/2"	80-200	60-150	445	40	0.96
P3335	1/2"	120-335	90-250	510	40	1.1
P4335	3/4"	120-335	90-250	510	40	1.14
P4500	3/4"	200-500	150-400	830	60	4
P4800	3/4"	300-800	225-600	1030	60	4.9
P41000	3/4"	400-1000	300-750	1030	60	4.9
P51000	1"	400-1000	300-750	1030	60	4.9
P51500	1"	600-1500	400-1100	1250	72	8.2
P52000	1"	800-2000	600-1500	1250	72	8.2
P53000	1"	1200-3000	800-2200	1250	72	9.5

*Unit is Lb.in

PH

Rectangular Shank Head Holder P Torque Wrench

for 9x12, 14x18, 24x32, 27x36mm rectangular shank head inserts



Optional fittings:

Item No.	Square Drive	Torque Range		Length mm	Width mm	Weight kg
		N.m	Lb.ft			
PH912	9X12	2.5-12	20-105*	245	28	0.38
PH920	9X12	8-20	60-180*	245	28	0.38
PH930	9X12	10-30	90-250*	285	28	0.52
PH960	9X12	20-60	15-45	305	28	0.66
PH9125	9X12	50-125	40-90	385	28	0.74
PH14200	14X18	80-200	60-150	440	32	0.86
PH14335	14X18	120-335	90-250	505	32	1
PH24500	24X32	200-500	150-400	830	56	4
PH24800	24X32	300-800	225-600	1030	56	4.9
PH241000	24X32	400-1000	300-750	1030	56	4.9
PH271500	27X36	600-1500	400-1100	1250	64	8
PH272000	27X36	800-2000	600-1500	1250	64	8
PH273000	27X36	1200-3000	800-2200	1250	64	9.3

*Unit is Lb.in

Note: Due to the product improvement, the technical parameters are subject to variation, please refer to the actual production from the factory.

100% Calibrated

Unique serial number for each torque wrench, corresponding to the certificate of calibration



Shockproof packaging

Specially designed for all series of "NovaTork" torque products

