




DS Model - Dial Torque Wrench


- Accuracy: +/-3% from 20% to 100% of Max.Torque (+/-4% accuracy for wrenches with capacities above 400N.m).
- Alloy steel structure, light weight and more durable.



- Peak torque holding function with included memory needle.



- DSM models are clockwise direction operation only.



- DSM-D models are clockwise & counter-clockwise direction operations.



- Metal Guard protects dial mechanism.



- Plastic guard protects the square drive.

100% Calibrated

Unique serial number for each torque wrench, corresponding to the certificate of calibration



Shockproof packaging

Specially designed for all series of "NovaTork" torque products



DSM

One-way Dial Torque Wrench

Select Metric and English scales by turning dial 180°

DS (English unit)

Item No.	Square Drive	Torque Range		Increment N.m	Length mm	Width mm	Weight kg	Extension
		N.m	Lb.ft					
DSM12	1/4"	0-2	0-18*	0.05	310	37	0.57	-
DSM13	1/4"	0-3	0-25*	0.05	310	37	0.57	-
DSM16	1/4"	0-6	0-50*	0.1	310	37	0.57	-
DSM18	1/4"	0-8	0-70*	0.2	310	37	0.57	-
DSM212	3/8"	0-12	0-100*	0.2	310	37	0.57	-
DSM217.5	3/8"	0-17.5	0-150*	0.25	310	37	0.57	-
DSM220	3/8"	0-20	0-175*	0.5	310	37	0.57	-
DSM225	3/8"	0-25	0-225*	0.5	310	37	0.57	-
DSM230	3/8"	0-30	0-250*	0.5	310	37	0.57	-
DSM235	3/8"	0-35	0-300*	0.5	400	37	0.76	-
DSM240	3/8"	0-40	0-350*	1	400	37	0.76	-
DSM250	3/8"	0-50	0-35	1	400	37	0.76	-
DSM260	3/8"	0-60	0-45	1	400	37	0.76	-
DSM3100	1/2"	0-100	0-70	2	480	37	0.91	-
DSM3120	1/2"	0-120	0-90	2	480	37	0.91	-
DSM3140	1/2"	0-140	0-100	2	480	37	0.91	-
DSM3200	1/2"	0-200	0-150	5	550	37	1.05	-
DSM3250	1/2"	0-250	0-175	5	550	37	1.05	-
DSM3275	1/2"	0-275	0-200	5	550	37	1.05	-
DSM3350	1/2"	0-350	0-250	5	550	37	1.05	-
DSM4400	3/4"	0-400	0-300	10	818	59	3.4	-
DSM4500	3/4"	0-500	0-350	10	818	59	3.4	-
DSM4600	3/4"	0-600	0-450	10	1192	59	6.4	1
DSM4800	3/4"	0-800	0-600	20	1192	59	6.4	1
DSM41000	3/4"	0-1000	0-700	20	1192	59	6.4	1
DSM51400	1"	0-1400	0-1000	20	1620	59	8.8	1
DSM52000	1"	0-2000	0-1500	50	1620	59	8.8	1

*Unit is Lb.in

* If need both directions, pls add D after item number, for example: DSM12D

DSM_D

Two-way Dial Torque Wrench

Scale with Metric and English unit, bi-directional operation

DS_D (English unit)

Item No.	Square Drive	Torque Range		Increment Lb.ft	Length mm	Width mm	Weight kg	Extension
		Lb.ft	N.m					
DS118	1/4"	0-18*	0-2	0.05	310	37	0.57	-
DS125	1/4"	0-25*	0-3	0.05	310	37	0.57	-
DS150	1/4"	0-50*	0-6	0.1	310	37	0.57	-
DS170	1/4"	0-70*	0-8	0.2	310	37	0.57	-
DS2100	3/8"	0-100*	0-12	0.2	310	37	0.57	-
DS2150	3/8"	0-150*	0-17.5	0.25	310	37	0.57	-
DS2175	3/8"	0-175*	0-20	0.5	310	37	0.57	-
DS2225	3/8"	0-225*	0-25	0.5	310	37	0.57	-
DS2250	3/8"	0-250*	0-30	0.5	310	37	0.57	-
DS2300	3/8"	0-300*	0-35	0.5	400	37	0.76	-
DS2350	3/8"	0-350*	0-40	1	400	37	0.76	-
DS235	3/8"	0-35	0-50	1	400	37	0.76	-
DS245	3/8"	0-45	0-60	1	400	37	0.76	-
DS370	1/2"	0-70	0-100	2	480	37	0.91	-
DS390	1/2"	0-90	0-120	2	480	37	0.91	-
DS3100	1/2"	0-100	0-140	2	480	37	0.91	-
DS3150	1/2"	0-150	0-200	5	550	37	1.05	-
DS3175	1/2"	0-175	0-250	5	550	37	1.05	-
DS3200	1/2"	0-200	0-275	5	550	37	1.05	-
DS3250	1/2"	0-250	0-350	5	550	37	1.05	-
DS4300	3/4"	0-300	0-400	10	818	59	3.4	-
DS4350	3/4"	0-350	0-500	10	818	59	3.4	-
DS4450	3/4"	0-450	0-600	10	1192	59	6.4	1
DS4600	3/4"	0-600	0-800	20	1192	59	6.4	1
DS4700	3/4"	0-700	0-1000	20	1192	59	6.4	1
DS51000	1"	0-1000	0-1400	20	1620	59	8.8	1
DS51500	1"	0-1500	0-2000	50	1620	59	8.8	1

*Unit is Lb.in

* If need both directions, pls add D after item number, for example: DS125D

Note: Due to the product improvement, the technical parameters are subject to variation, please refer to the actual production from the factory.

