

Induction cooker 3500 D

239711

Housing made of stainless steel. Continuous low-power heating ensures even cooking and helps to eliminate the risk of burning. Digital power, temperature, and timer setting via touch-sensitive controls. With easily cleanable grease filter. Double fan system ensures efficient cooling, allowing safe use over extended periods. Suitable for pans with bottom diameter between 140 and 280 mm. Height adjustable feet. Maximum load of the induction cooker: 20 kg.



Specifications

Voltage	: 230
Rated Frequency (Hz)	: 50 Hz, 60 Hz
Temp range from (°C)	: 60°C
Temp range to (°C)	: 240°C
Unit temperature	: Celsius
Heating element	: Induction
Electrician needed	: No
Marketing Packaging Type	: Box
Length (mm)	: 342
Width (mm)	: 431
Height (mm)	: 116
Power (input) (W)	: 3500
Programmable	: No
Measurements	: 342x431x(H)116
Adapter plug CH	: 16A
Quantity of plugs	: 1
Main materials	: Metals
Materials	: Stainless steel

Transport specifications

EAN	: 8711369239711
Intrastat code	: 84198180
Gross weight (kg)	: 8.16
Net weight (kg)	: 7.09
Export carton length (mm)	: 542
Export carton width (mm)	: 429
Export carton height (mm)	: 330
Quantity per export carton	: 2
Sales units per pallet	: 32
Plastic packaging (gram)	: 186

HENDI B.V.
 Innovatielaan 6
 6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
 ul. Firmowa 12
 62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
 Ehrling 15
 5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
 Str. 13 decembrie 94A, Hala 14
 Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
 5 Metsovou Str.
 18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
 Via Leonardo da Vinci 4
 39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu