

Induction cooker 3500 D XL

239698

Housing made of stainless steel. Continuous low-power heating ensures even cooking and helps to eliminate the risk of burning. Digital power, temperature, and timer setting via touch-sensitive controls. With easily cleanable grease filter. Double fan system ensures efficient cooling, allowing safe use over extended periods. Suitable for pans with bottom diameter between 160 and 300 mm. Height adjustable feet. Maximum load of the induction cooker: 20 kg.



Specifications

Usage area	: Kitchen
Voltage	: 230
Rated Frequency (Hz)	: 50 Hz, 60 Hz
Temp range from (°C)	: 35°C
Temp range to (°C)	: 240°C
Unit temperature	: Celsius
Heating element	: Induction
Electrician needed	: No
Marketing Packed per	: 1
Marketing Packaging Type	: Box
Length (mm)	: 390
Width (mm)	: 490
Height (mm)	: 120
Power (input) (W)	: 3500
Programmable	: No
Measurements	: 390x490x(H)120
Main materials	: Metals
Materials	: Stainless steel

Transport specifications

EAN	: 8711369239698
Intrastat code	: 84198180
Gross weight (kg)	: 9.13
Net weight (kg)	: 7.88
Export carton length (mm)	: 585
Export carton width (mm)	: 462
Export carton height (mm)	: 345
Quantity per export carton	: 2
Sales units per pallet	: 24
Plastic packaging (gram)	: 242

HENDI B.V.
Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.
ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH
Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.
Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA
5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.
Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu