



## Power Strip XO CPVT6RD-M (EU)

1x powerCON TRUE1 IN – 6x powerCON® TRUE1® TOP  
OUT - Power Meter



Power Strip Xtreme Outdoor (XO) is a compact distribution solution for mobile outdoor applications where power meter is required. Rugged EASYLEN® housing is ideally suited for outdoor usage and demanding applications under harsh conditions. 1x powerCON® TRUE1® TOP In, 6x powerCON® TRUE1® TOP Out, Power Meter.



## Features & Benefits

- ✓ Extreme robust and safe EASYLEN® housing with leather grain texture
- ✓ Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- ✓ Flame retardant (UL94-V2) and non-conductive housing material
- ✓ High outdoor protection (IP65, IK, ..)
- ✓ Meter with protected and lit voltage and current consumption display
- ✓ Light weight, compact and stackable housing design
- ✓ Versatile mounting options

## Market & Applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Mobile application: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios

## Article Variations

| Article name | Details                                                                    | Order code |
|--------------|----------------------------------------------------------------------------|------------|
| CPVT6RD-M    | IN: 1 x powerCON® TRUE1® TOP - OUT: 6 x powerCON® TRUE1® TOP – Power Meter | 1035587    |

## Technical Information

|                |                                                           |
|----------------|-----------------------------------------------------------|
| Input device   | 1x powerCON®TRUE1®TOP with self-closing caps              |
| Output device  | 6x powerCON®TRUE1®TOP with self-closing caps              |
| Daisy chaining | 1x powerCON®TRUE1®TOP with self-closing caps              |
| Power meter    | Protected and lit screen with current and voltage display |

## Electrical

|                                       |                     |
|---------------------------------------|---------------------|
| Contact resistance / protection class | Protection class II |
| Dielectric strength                   | 0,5 kV / mm         |
| Rated voltage                         | 250V AC             |
| Rated Current                         | 16A (USA: 20A)      |
| Number of electrical contacts         | 2 + PE              |
| Phases                                | single-phase        |

## Mechanical

|                         |                                                       |
|-------------------------|-------------------------------------------------------|
| Lifetime                | > 5000 Mating cycles per connector                    |
| Dimensions              | 380 x 91.2 x 77 mm                                    |
| Conductor cross section | 2.08 mm²                                              |
| Weight                  | 1.27 kg                                               |
| Mounting options        | Truss clip, mounting wholes for pegging or suspension |

|         |         |
|---------|---------|
| Housing | Easylen |
| Color   | black   |

| Environmental           |                  |
|-------------------------|------------------|
| Standards compatibility | UL94-V2          |
| Protection class        | IP65             |
| Temperature range       | -25 °C bis +50°C |