



Power Turtle Xtreme Outdoor CPTM-S1-T6

IN: 11x Socapex 419 – OUT: 6x powerCON® TRUE1® TOP

Power Turtle Multicore are extremely rugged compact distribution boxes which allow significant reduction of the cabling volume, effort and cost due to the multicore input. It is ideally suited for outdoor usage and demanding mobile applications.

Features & Benefits

- **Reduction of cabling volume and effort** due to Socapex 419 compatible multipin connector. And Even more reduction of cabling due to the versions with 12x Outs
- **Very compact design:** flat design, lateral connector arrangement, applications with restricted space.
- **Versatile mounting options:** pegs, suspension, truss clamp
- **High durability & protection:** Rugged Easylen® housing with high IK, IP65 with Socapex 419 in mated condition, self-closing caps, lateral connector arrangement, flame retardant & non-conductive housing material
- **Easy transport & handling:** stackable with other Power Turtles, lightweight, fully lockable

Markets & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

Ordering information

Article name	Details	Order code
CPTM-S1-T6	IN: 1x Socapex 419 compatible OUT: 6x powerCON TRUE1 TOP	1028858

Technical Information

Product

Input device	1x Socapex 419 compatible (6 channels)
Output device	6x powerCON® TRUE1® TOP with self-closing caps
Daisy chaining	powerCON® TRUE1® TOP with self-closing caps

Electrical

Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	16A
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical

Dimensions	225 x 166 x 87mm
Weight	1,4 kg
Conductor cross section	2,08 mm ²
Mounting options	Truss clamp (M10), mounting wholes for pegging or suspension
Type of construction	Stackable

Material

Housing	Easylen
Color	black

Environmental

Flammability acc. to UL 94	V-2
Protection class	IP65 with Socapex 419 in mated condition
Temperature range	-25 °C bis +40 °C